

## *Premium touch screen for your home*

The Akuvox S562W-2 multifunctional communicator, with a Linux operating system, provides audio and video communication with door phones via SIP 2.0 protocol. It delivers the ultimate touch screen experience in an unobtrusive, space-saving design featuring a brilliant 7-inch capacitive touch screen display.



## *At a Glance*

- Ultra-clear, stylish appearance;
- Linux OS;
- 7-inch capacitive touch screen with energy saving mode;
- Completely solve the stability problem of Wi-Fi with Wi-Fi 6;
- Two-way audio communication with other units in the 2-Wire IP network;
- Powered by NS-2 or external source;
- Super long transmission distance via 2-wire cable
- Support US or European electrical wall box mounting;
- Complies with SIP standard for easy integration in every SIP capable PBXes;

## Physical & Power

- |  |  |
|--|--|
| • Front panel: Plastic                   | • Microphone: -42dB                    |
| • RAM / ROM: 128MB / 128MB               | • Speaker: 4Ω / 2W                     |
| • Display: 7 Inch IPS LCD                | • 2-Wire Port: 2                       |
| • Screen: 7 Inch Capacitive Touch Screen | • Ethernet Port: 1xRJ45, 10/100Mbps    |
| • Wi-Fi: IEEE802.11 b/g/n/ax, @2.4GHz    | • Adaptive Power: 12V DC Connector     |
| • RS485 Port: 1                          | • Tamper Resistant: Support            |
| • Relay Out: 1                           | • Installation: Wall-mounted & Desktop |
| • Bell in: 1                             | • Dimension: 216.4x118.8x21.7mm        |
| • Alarm Input: 8                         | • Working Humidity: 10~90%             |
|  | • Working Temperature: -10°C ~ +45°C   |
|  | • Storage Temperature: -20°C ~ +70°C   |