Akuvox S563W Datasheet

Premium touch screen for your home

The Akuvox S563W Indoor monitor with an Android 12 operating system, provides an unparalleled audio—visual intercom experience with a high level speaker. It delivers the ultimate touch screen experience in an unobtrusive, space—saving design featuring a brilliant 8—inch capacitive touch screen display.

At a Glance

- Strong compatibility with Android 12 OS;
- Two-way audio communication with other units in the network;
- Complies with SIP standard for easy integration in every SIP capable PBXes;
- Powered by PoE or external source;
- Support Voice Changer to protect the children and women living alone;
- Support US or European electrical wall box mounting;
- Built—in smart voice assistant;

Physical & Power

• Front panel: Plastic

• RAM / ROM: 2GB / 8GB

• Display: 8 Inch IPS LCD

• Screen: 8 Inch capacitive touch screen

• Wi-Fi: IEEE802.11 b/g/n

• Bluetooth: 4.2

• RS485 Port: Support

• Relays Out: 1

• Bell in: 1

• Alarm Input: 8

• Microphone: Dual microphones, -26dB

 \bullet Speaker: Quad speakers, 4Ω / 2W

• Ethernet Ports: 2xRJ45, 10/100Mbps adaptive

• 802.3af Power-over-Ethernet

• 12V DC Connector (if not using PoE)

• Tamper Resistant: Support

• Installation: Wall-mounted & Desktop

• Dimension: 216.2x124.4x22.1 mm

• Working Humidity: 10~90%

• Working Temperature: -10° C ~ +45° C

• Storage Temperature: -20° C ~ +70° C

Akuvox S563W Datasheet

Touch Screen Display

• Display Mode: Normally black, Transmissive

• LCD Size: 8 inch (Diagonal)

• Aspect Ratio: 16:10

• Resolution: 1280x800

• Contrast ratio: 1200:1

• Luminance: 310 cd/m²

• Viewing Angle: 80° Left, 80° Right,

80° Upper, 80° Lower

• Touch Screen: Projected capacitive

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711 μ, G.729
- Broadband audio codec: G.722
- DTMF: In—band, out—of—band DTMF (RFC2833), SIP
- Fcho Cancellation
- Voice Activation Detection
- Comfort Noise Generator
- Automatic Gain Control

Video

• Streaming formats: H.263 & H.264

Networking

Protocols support: IPv4, HTTP, HTTPS, FTP, TFTP,
SNMP, DNS, SNTP, RTSP, SRTP, RTP, TCP, UDP,

TLS, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto—Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Firmware upgrade
- System logs (include door access logs)

Voice Assistant

- Voice pickup distance up to 5 meters
- Voice recognition accuracy up to 95%
- Privacy protection with native voice data
- Support English

Application Scenario

- Villas
- Apartment complexes
- Home automation systems
- Modern interiors