

Network Audio Bridge Amplifier

IP-1015BX



- Supports PoE/PoE+
- 10/100 BASE-T Ethernet (Default IP: 192.168.1.99)
- Micro SD card slot

		IP-1015BX	
Amplifier			
Rated output power (8Ω, 1kHz sine wave)		4.5W(PoE 802.3af)	10W(PoE+ 802.3at)
Frequency response (1W @ 8Ω, ±1dB)		20Hz - 20kHz	
THD+N (20Hz HPF, AES17 LPF, 8Ω)		Less than 0.3%	
Line output			
Maximum audio output		+6dBV ± 3dB	
Frequency response		20Hz - 20kHz (+1/-3dB)	
THD+N (20Hz HPF, AES17 LPF)		Less than 0.1%	
S/N (20Hz HPF, AES17 LPF, A-WTD)		Better than 85dB	
Contact I/O			
Contact Input (1CH)		Dry contact	
Contact Output (1CH)		Dry contact (N.O : Normally Open)	
Storage			
Micro SD		MAX: 32GB	
Network			
Ethernet		10/100 BASE-TX PoE	
General			
Power		PoE (IEEE 802.3af, IEEE 802.3at)	
Operating temperature		-20°C ~ +50°C	
Power consumption		PoE (802.3af) : 44~57 VDC, Max 12.95W PoE+ (802.3at) : 50~57 VDC, Max 25.5W	
Weight (SET)		0.24kg/0.53lb	
Dimensions (SET)		123(W) x 80(H) x 30.6(D)mm 4.84(W) x 3.14(H) x 1.2(D)in	