

# Choosing the right InterM Stereo Power Amplifier



Model	Number of Channels	Power Output @ 2Ω per channel	Power Output @ 4Ω per channel	Power Output @ 8Ω per channel	Power Output Bridged Mono 4Ω	Power Output Bridged Mono 8Ω	Input Connectors	Output Connectors	Frequency Response	Input Sensitivity	Cooling	Protection	Accessories	Power 230v AC, 50Hz	Rack Mount Height	Weight (Kg)	Dimensions (mm)
<b>R150+</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)		75W	50W		150W	XLR & 6.35mm Jack	Speakon & Binding Posts	✓ 20Hz~20kHz	0dB / 0.775mV	Convection			✓	2U	7.2	W: 482 H: 88 D: 317
<b>R300+</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)		150W	100W		300W	XLR & 6.35mm Jack	Speakon & Binding Posts	✓ 20Hz~20kHz	0dB / 0.775mV	Convection			✓	2U	8.4	W: 482 H: 88 D: 317
<b>R500+</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)		250W	160W		500W	XLR & 6.35mm Jack	Speakon & Binding Posts	✓ 20Hz~20kHz	0dB / 0.775mV	Convection			✓	2U	10.4	W: 482 H: 88 D: 317
<b>V2-1000</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)	550W	300W	170W	1100W	650W	XLR & 6.35mm Jack	Speakon	✓ 20Hz~20kHz	1v	Variable Speed Fan	Full Short Circuit, Thermal Protection		✓	2U	10.7	W: 482 H: 88 D: 407
<b>V2-2000</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)	850W	500W	280W	1700W	1000W	XLR & 6.35mm Jack	Speakon	✓ 20Hz~20kHz	1v	Variable Speed Fan	Full Short Circuit, Thermal Protection		✓	2U	10.9	W: 482 H: 88 D: 407
<b>V2-3000</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)	1400W	900W	500W	3000W	1800W	XLR & 6.35mm Jack	Speakon	✓ 20Hz~20kHz	1v	Variable Speed Fan	Full Short Circuit, Thermal Protection		✓	2U	12	W: 482 H: 88 D: 407
<b>V2-4000</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)	1800W	1150W	650W	3800W	2400W	XLR & 6.35mm Jack	Speakon	✓ 20Hz~20kHz	1v	Variable Speed Fan	Full Short Circuit, Thermal Protection		✓	2U	12.1	W: 482 H: 88 D: 407
<b>QD-4240</b> <small>BUY NOW</small>	<b>Quad</b> (4 channels)		60W	40W		120W	Combi XLR / 6.35mm Jack	Binding Posts	✓ 20Hz~50kHz	0.775mV	Variable Speed Fan		OT-4240	✓	2U	11.5	W: 482 H: 88 D: 369
<b>QD-4480</b> <small>BUY NOW</small>	<b>Quad</b> (4 channels)		120W	80W		240W	Combi XLR / 6.35mm Jack	Binding Posts	✓ 20Hz~50kHz	0.775mV	Variable Speed Fan		OT-4480	✓	2U	15.5	W: 482 H: 88 D: 369
<b>QD-4960</b> <small>BUY NOW</small>	<b>Quad</b> (4 channels)		240W	170W		480W	Combi XLR / 6.35mm Jack	Binding Posts	✓ 20Hz~50kHz	0.775mV	Variable Speed Fan		OT-4960	✓	2U	17	W: 482 H: 88 D: 369
<b>V2-1000N</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)	550W	300W	170W	1100W	650W	Combi XLR / 6.35mm Jack & Phoenix Screw Terminal	Speakon	✓ 20Hz~20kHz	1v / 32dB / 26dB	Variable Speed Fan	Full Short Circuit, Thermal Protection	Remote Control Software Download	✓	2U	10.7	W: 482 H: 88 D: 407
<b>V2-2000N</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)	850W	500W	280W	1700W	1000W	Combi XLR / 6.35mm Jack & Phoenix Screw Terminal	Speakon	✓ 20Hz~20kHz	1v / 32dB / 26dB	Variable Speed Fan	Full Short Circuit, Thermal Protection	Remote Control Software Download	✓	2U	10.9	W: 482 H: 88 D: 407
<b>V2-3000N</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)	1400W	900W	500W	3000W	1800W	Combi XLR / 6.35mm Jack & Phoenix Screw Terminal	Speakon	✓ 20Hz~20kHz	1v / 32dB / 26dB	Variable Speed Fan	Full Short Circuit, Thermal Protection	Remote Control Software Download	✓	2U	12	W: 482 H: 88 D: 407
<b>V2-4000N</b> <small>BUY NOW</small>	<b>Stereo</b> (2 channels)	1800W	1150W	650W	3800W	2400W	Combi XLR / 6.35mm Jack & Phoenix Screw Terminal	Speakon	✓ 20Hz~20kHz	1v / 32dB / 26dB	Variable Speed Fan	Full Short Circuit, Thermal Protection	Remote Control Software Download	✓	2U	12.1	W: 482 H: 88 D: 407