

Choosing the right InterM Mixer Amplifier



Model	Power Output 100v (RMS)	Power Output Low Z	Type	Mic/Line inputs	Inputs	Misc.	Line Out	Phantom Power	Priority Structure	Remote Chime/Mute	Rack Mount Options	Frequency Response	AC Power	Power Consumption	DC Power /24v DC	Weight (Kg)	Dimensions (mm)
PA935N BUY NOW	35W	8Ω/4Ω	Analogue	3	1x Mic (6.35mm Jack), 1x Mic/Line (6.35mm Jack), 1x Mic/Aux-SAT (6.35mm Jack/2x RCA) & Tel In (Screw Terminal)				VOX on Tel In and Mic 1		BKT-PA935	80Hz-15kHz	230v AC/50Hz	40W		4.4	W: 290 H: 76 D: 185
PA1000B BUY NOW	30W	8Ω/4Ω	Analogue	3	2x Mic (3Pin XLR/6.35mm Jack), 1x Aux (6.35mm Jack) & Tel In (Screw Terminal)		1v/600Ω		VOX on Tel In and Mic 1	via Screw Terminal	BKT-1000B	60Hz-20kHz	230v AC/50Hz	80W		4.6	W: 300 H: 88 D: 268
A60 BUY NOW	60W	4Ω	Analogue	5	3x Mic (Combi XLR/6.35mm Jack) and 2x AUX (Stereo RCA)				VOX on Mic 1		BKT-A120	80Hz-16kHz	230v AC/50Hz	75W		8.9	W: 420 H: 88 D: 320
A120 BUY NOW	120W	4Ω	Analogue	5	3x Mic (Combi XLR/6.35mm Jack) and 2x AUX (Stereo RCA)				VOX on Mic 1		BKT-A120	80Hz-16kHz	230v AC/50Hz	105W		10.3	W: 420 H: 88 D: 320
MA106 BUY NOW	60W	4Ω	Class-D	3	1x Mic (6.35mm Jack/3 Pin XLR), 1x Mic/Line (6.35mm Jack), 1x Aux (6.35mm Jack/2x RCA) & Tel In (Screw Terminal)			Mic 1 / switched	VOX on Tel In and Mic 1		BKT-MA106	80Hz-15kHz	230v AC/50Hz	24W		3	W: 300 H: 44 D: 230
MA110 BUY NOW	100W	4Ω	Class-D	3	1x Mic (6.35mm Jack/3 Pin XLR), 1x Mic/Line (6.35mm Jack), 1x Aux (6.35mm Jack/2x RCA) & Tel In (Screw Terminal)			Mic 1 / switched	VOX on Tel In and Mic 1		BKT-MA106	80Hz-15kHz	230v AC/50Hz	24W		3	W: 300 H: 44 D: 230
PA2000A BUY NOW	60W	8Ω/4Ω	Analogue	6	5x Mic/Line (3 Pin XLR), 1x Aux (2x RCA) & Tel In (Screw Terminal)	5 Band Graphic EQ	-6dB/600Ω		VOX on Tel In Mic/Line 1 and Mic/Line 2	via Screw Terminal	BKT-2000A	60Hz-20kHz	230v AC/50Hz	95W		10	W: 420 H: 100 D: 320
PA4000A BUY NOW	120W	8Ω/4Ω	Analogue	6	5x Mic/Line (3 Pin XLR), 1x Aux (2x RCA) & Tel In (Screw Terminal)	5 Band Graphic EQ	-6dB/600Ω		VOX on Tel In Mic/Line 1 and Mic/Line 2	via Screw Terminal	BKT-PAM	60Hz-20kHz	230v AC/50Hz	120W		12	W: 420 H: 133 D: 320
PA6000A BUY NOW	240W	8Ω/4Ω	Analogue	6	5x Mic/Line (3 Pin XLR), 1x Aux (2x RCA) & Tel In (Screw Terminal)	5 Band Graphic EQ	-6dB/600Ω		VOX on Tel In Mic/Line 1 and Mic/Line 2	via Screw Terminal	BKT-PAM	60Hz-20kHz	230v AC/50Hz	240W		13.5	W: 420 H: 133 D: 320
PAM120A BUY NOW	120W	4Ω	Analogue	6	6x Mic/Line (3 Pin XLR) & Tel In (Screw Terminal)		-6dB/600Ω	Mic 1 & 2/ Switched	VOX on Tel In Mic/Line 1 and Mic/Line 2	via Screw Terminal	BKT-PAM (supplied)	80Hz-20kHz	230v AC/50Hz	300W		13	W: 420 H: 132 D: 360
PAM340A BUY NOW	340W		Analogue	6	6x Mic/Line (3 Pin XLR) & Tel In (Screw Terminal)		-6dB/600Ω	Mic 1 & 2/ Switched	VOX on Tel In Mic/Line 1 and Mic/Line 2	via Screw Terminal	BKT-PAM (supplied)	80Hz-20kHz	230v AC/50Hz	620W		13.5	W: 420 H: 132 D: 360
PAM480A BUY NOW	480W		Analogue	6	6x Mic/Line (3 Pin XLR) & Tel In (Screw Terminal)		-6dB/600Ω	Mic 1 & 2/ Switched	VOX on Tel In Mic/Line 1 and Mic/Line 2	via Screw Terminal	BKT-PAM (supplied)	80Hz-20kHz	230v AC/50Hz	880W		15.5	W: 420 H: 132 D: 360
PMU60N BUY NOW	60W	4Ω	Class-D	6	5x Mic/Line (1-3 = 3 Pin XLR/Phoenix Screw Terminal, 4-5 = 6.35mm Jack), 1x AUX (2x RCA) & Tel In (Screw Terminal)	Network Streamer, USB Media Player, VCA Remote	0dB/10kΩ	Inputs 1-3 / Switched	VOX on Tel In Mic/Line 1 and Mic/Line 3	via Screw Terminal	BKT-A120	80Hz-15kHz	230v AC/50Hz	38W		5.4	W: 420 H: 88 D: 328
PMU120N BUY NOW	120W	4Ω	Class-D	6	5x Mic/Line (1-3 = 3 Pin XLR/Phoenix Screw Terminal, 4-5 = 6.35mm Jack), 1x AUX (2x RCA) & Tel In (Screw Terminal)	Network Streamer, USB Media Player, VCA Remote	0dB/10kΩ	Inputs 1-3 / Switched	VOX on Tel In Mic/Line 1 and Mic/Line 3	via Screw Terminal	BKT-A120	80Hz-15kHz	230v AC/50Hz	50W		6.7	W: 420 H: 88 D: 328