

Choosing the right InterM Power Amplifier

| Model | Type | Power Output 100v | Power Output Low Z | Line In | Line Out | Frequency Response | Priority Input | High Pass Filter | Remote Power On/Off | Cooling | AC Power | 1/8 Power Consumption | DC Power / 24v DC | Rack Mount Height | Weight (Kg) | Dimensions (mm) |
|---|----------------|-------------------|--------------------|------------------|------------------|--------------------|------------------|--------------------------|-----------------------|------------|----------|-----------------------|-------------------|-------------------|-------------|----------------------------|
| DPA1200S BUY NOW | Class-D / SMPS | 1200W | | Phoenix Terminal | Phoenix Terminal | 60Hz–20kHz | Phoenix Terminal | | ✓ Phoenix Terminal | Convection | ✓ | 250W | ✓ | 2U | 7.7 | W: 482 H: 88 D: 450 |
| DPA900S BUY NOW | Class-D / SMPS | 900W | | Phoenix Terminal | Phoenix Terminal | 60Hz–20kHz | Phoenix Terminal | | ✓ Phoenix Terminal | Convection | ✓ | 250W | ✓ | 2U | 7.7 | W: 482 H: 88 D: 450 |
| DPA600D BUY NOW | Class-D / SMPS | 2 x 600W | | Phoenix Terminal | Phoenix Terminal | 50Hz–20kHz | Phoenix Terminal | | ✓ Phoenix Terminal | Convection | ✓ | 130W | ✓ | 2U | 6.6 | W: 482 H: 88 D: 450 |
| DPA600S BUY NOW | Class-D / SMPS | 600W | | Phoenix Terminal | Phoenix Terminal | 50Hz–20kHz | Phoenix Terminal | | ✓ Phoenix Terminal | Convection | ✓ | 130W | ✓ | 2U | 6.6 | W: 482 H: 88 D: 397 |
| DPA300Q BUY NOW | Class-D / SMPS | 4 x 300W | | Phoenix Terminal | Phoenix Terminal | 50Hz–20kHz | Phoenix Terminal | | ✓ Phoenix Terminal | Convection | ✓ | 130W | ✓ | 2U | 6.5 | W: 482 H: 88 D: 450 |
| DPA300T BUY NOW | Class-D / SMPS | 3 x 300W | | Phoenix Terminal | Phoenix Terminal | 50Hz–20kHz | Phoenix Terminal | | ✓ Phoenix Terminal | Convection | ✓ | 130W | ✓ | 2U | 6.5 | W: 482 H: 88 D: 450 |
| DPA300D BUY NOW | Class-D / SMPS | 2 x 300W | | Phoenix Terminal | Phoenix Terminal | 50Hz–20kHz | Phoenix Terminal | | ✓ Phoenix Terminal | Convection | ✓ | 130W | ✓ | 2U | 6.5 | W: 482 H: 88 D: 397 |
| DPA300S BUY NOW | Class-D / SMPS | 300W | | Phoenix Terminal | Phoenix Terminal | 50Hz–20kHz | Phoenix Terminal | | ✓ Phoenix Terminal | Convection | ✓ | 130W | ✓ | 2U | 6.5 | W: 482 H: 88 D: 397 |
| DPA-430H BUY NOW | Class-D / SMPS | 4 x 300W | | Phoenix Terminal | Phoenix Terminal | 65Hz–20kHz | | 400Hz (1W, -3dB ±2dB) | ✓ | Fan | ✓ | 250W | | 1U | 9.6 | W: 482 H: 44 D: 420 |
| DPA-230DC BUY NOW | Class-D / SMPS | 2 x 300W | | Phoenix Terminal | Phoenix Terminal | 65Hz–20kHz | | 400Hz (1W, -3dB ±2dB) | ✓ | Fan | ✓ | 150W | ✓ | 1U | 8.3 | W: 482 H: 44 D: 420 |
| DPA-130DC BUY NOW | Class-D / SMPS | 300W | | Phoenix Terminal | Phoenix Terminal | 65Hz–20kHz | | 400Hz (1W, -3dB ±2dB) | ✓ | Fan | ✓ | 150W | ✓ | 1U | 6.8 | W: 482 H: 44 D: 420 |
| PA6348 BUY NOW | Analogue | 480W | 1 x 4Ω | 1 x XLR/F | 1 x XLR/M | 70Hz–18kHz | | -3dB/400Hz | | Fan | ✓ | 600W | ✓ | 3U | 22 | W: 482 H: 132 D: 280 |
| PA6336 BUY NOW | Analogue | 360W | 1 x 4Ω | 1 x XLR/F | 1 x XLR/M | 70Hz–18kHz | | -3dB/400Hz | | Fan | ✓ | 450W | ✓ | 3U | 19 | W: 482 H: 132 D: 280 |
| PA6312 BUY NOW | Analogue | 120W | 1 x 4Ω | 1 x XLR/F | 1 x XLR/M | 70Hz–18kHz | | -3dB/400Hz | | Fan | ✓ | 130W | ✓ | 3U | 14 | W: 482 H: 132 D: 280 |
| PA2312 BUY NOW | Analogue | 2 x 120W | 2 x 4Ω | 2 x XLR/F | 2 x XLR/M | 70Hz–18kHz | | -3dB/400Hz | | Fan | ✓ | 290W | ✓ | 3U | 20 | W: 482 H: 132 D: 280 |