

## NC806CS

Overdoor Light c/w Sounder



### Overview

Provides audible and visual indication of 800 Series Alarm calls outside bedrooms, WCs and any other area fitted with an 800 Series calling device.

Indicates Standard calls via a constant tone/constant red light and Emergency calls via a pulsing tone/pulsing red light.

Dual red LEDs and triangular diffuser make it highly visible from a distance.

Mounts on a standard UK 25mm single gang flush or surface back box.

Can also be used as an 'area indicator' at corridor junctions, staff workstations, etc.

Finished in tough, durable ABS plastic.

Also available as part of the NC951 Accessible Toilet Alarm kit.

Stainless steel version also available.

### Technical Specifications

---

Quiescent current	0mA (none).
-------------------	-------------

---



<b>Alarm current</b>	Determined by the type of control equipment and number / type of field devices connected to the system.
<b>Indicators</b>	Dual ultra-bright red Alarm LEDs (lit constantly for standard calls, intermittently for emergency calls).
<b>Controls</b>	None (the device is controlled by the master calling device it is connected to).
<b>Connections</b>	1 (Signal); -Ve (Negative); +Ve (Positive).
<b>Onboard Sounder</b>	Yes. Sounds constantly for standard calls, intermittently for emergency calls.
<b>Onboard Infrared Receiver</b>	No.
<b>Product dimensions (mm)</b>	87 W x 87 H x 68 D mm. Mounts on a UK 25mm single gang back box.
<b>Construction &amp; finish</b>	Plastic.
<b>IP Rating</b>	IP41.
<b>Weight</b>	52g.
<b>Operating conditions/temperature</b>	-5°C to +40°C. Max. relative humidity 95% non-condensing.





CIE-Group Ltd  
3 Widdowson Close  
Blenheim Ind Est  
Bulwell  
Nottingham  
NG6 8WB

Email: [info@cie-group.com](mailto:info@cie-group.com)  
Telephone: 0115 9770075

