

NC807C

Ceiling Pull Unit



Overview

Can be used to generate a standard call on an 800 Series Conventional Call System.

Typically wired as a slave to an 800 Series Call Point or Reset Point so that its calls can be cancelled.

Supplied with 3m of red nylon pull cord and two red open-sided triangular bangles for ease of use by the infirm.

Red confidence LED and diffuser emits a bright red glow over a wide area to reassure the user that a call has been made.

Surface mountable.

Base fits 16mm conduit and BESA centres.

Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and the number / type of field devices connected to the system.
Indicators	Red reassurance LED/diffuser (active in Alarm).
Controls	Red pull cord c/w two red open-sided triangular bangles.



Onboard Sounder	No.
Product dimensions (mm)	93mm diameter x 27mm deep. Designed for ceiling mounting only. Base fits 16mm conduit and BESA centres.
Construction & finish	Plastic.
IP Rating	IP21.
Weight	55g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.





CIE-Group Ltd
3 Widdowson Close
Blenheim Ind Est
Bulwell
Nottingham
NG6 8WB

Email: info@cie-group.com
Telephone: 0115 9770075

