

NC894DKB

Isolatable Monitoring Point Button Reset



Overview

A keyswitch-isolatable monitoring point c/w magnetic door contacts for use with C-TEC's 800 Series Call System.

Can be used to monitor any device with a normally open or normally closed switch.

Triggers a Standard call when activated

Typical uses include monitoring fire exits, drug cupboards, store rooms, etc.

Isolation keyswitch temporarily turns off the device's monitoring function when in the ISOLATED position.

Red reassurance LED illuminates when a call is made.

Includes a RESET button for cancelling calls.

Mounts on a standard UK 25mm single gang flush or surface back box.

Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.



Indicators	Red Reassurance LED (lit constant for Standard calls).
Controls	Isolation keyswitch (switches monitoring off when ISOLATED); Reset button (cancels Standard calls made from the monitoring point and from devices wired on the same Zone).
Connections	SIG (Signal); RC (Signal); -Ve (Negative); SW- (Switched Negative); NO (normally open connection); NC (normally closed connection); T (trigger connection). PLK1 link for n/o or n/c operation.
Onboard 6.35mm Remote Jack Socket	No.
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 35 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	84g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.





CIE-Group Ltd
3 Widdowson Close
Blenheim Ind Est
Bulwell
Nottingham
NG6 8WB

Email: info@cie-group.com
Telephone: 0115 9770075

