

# X7HD



## Door Entry Monitoring Panel

### The new X7HD is a multi-functional Touchscreen Door Entry Monitoring Panel featuring Android operating system.

Providing high quality audio and HD video communication for door intercom and door phone systems via SIP 2.0 protocol, the **X7HD** is ideal for residential / MDU door entry.

This IP-connected door answering panel provides the ultimate touch-screen experience in an unobtrusive, space-saving design featuring 7" HD, capacitive touchscreen display.

Using a highly intuitive, Android-based operating system, the user has the ability for 2-way communication with visitors to the door before allowing access – with HD video images and high quality audio of any visitors. If the user is happy to allow the visitor in, they can remotely unlock internal / external doors (using IP-addressable remote door locks), switch on corridor lights, etc – ideal in apartment living, large homes or buildings where the visitor does not need to be met at the door.

The X7HD is designed for interior use only (normally wall-mounted internally at strategic door positions) and is ideal for integration as part of a IP-connected intercom or access control system. Ideal for use in apartment complexes, home automation systems, modern interiors, large villas and high specification office environments. Finished in black.

#### Touch Screen Display

Display Type:	Active matrix TFT, transmissive type
Size:	7 inch (176mm) diagonal
Aspect ratio:	16:9
Resolution:	1024x600
Brightness:	300 nits (cd/m sq)
Contrast:	800:1
Colour Depth:	24-bit, 16M colours
Illumination:	Edgelit LED
Viewing Angle:	±70° horizontal, ±70° vertical
Touch Screen:	Projected Capacitive

#### Audio / Video

Audio features:	Built-in microphone & speaker
Streaming formats:	H.264

#### Memory

Memory Capacity:	RAM: 1Gb / Flash: 8Gb
------------------	-----------------------

#### Interface

Ethernet:	2x10/100Mbps ports, auto-switching, auto-discovery, auto-negotiating, full/half duplex, DHCP
Relay Out:	1x relay out (NO, COM, NC)
Alarm In:	8x Alarm input terminals
Bell In:	1x Bell input terminal
RS485:	1x RS485 communication port

Temperature:	14° to 112° F (-10° to 45°C)
Humidity:	10% to 90% (non condensing)
Dimensions:	200(W) x 132(H) x 17.5(D) mm

#### Features:

- 7" capacitive touch screen
- Luxury door entry / communication touch screen
- Android operating system; simple to use, control and configure
- High definition view of visitors at the door
- Remote door unlocking
- Receive video and audio from connected indoor / outdoor Access / Intercom Terminals
- Easily integrates with SIP Systems
- Power supply via PoE or adapter