



Clever Little Box



• **AVID: In-wall Stereo Amplifier 2x 12W**

The AVID In-wall Amplifier from Clever Little Box is a stylish, but discreet 2 x 12W stereo amplifier for in-wall or dado conduit mounting.

An ideal solution for AV and single-room voice or sound reinforcement applications, the AVID Stereo Amplifier is fitted into a 2-gang wallplate and features 3 x audio source inputs (3.5mm jack, 2 x RCA and screw terminal), line level sensitivity switch and bright LED display.

Supplied as standard, the AVID remote control unit provides ON/OFF, volume, tone and balance control.

The AVID compact amplifier is ideal for applications such as classrooms, boardrooms, meeting or demo rooms and even in domestic home installations.

**Features:**

- Stereo amplifier fitted to UK 2-gang Wallplate
- New higher power 2 x 12W output (RMS)
- 3 x Input Sources; Stereo Phono, 3.5mm Stereo Jack (Jack has priority) and Wired Input Terminal (on rear PCB)
- Line Level Sensitivity Switch
- Control of ON/OFF and volume via illuminated push buttons located on the front panel
- Infrared remote control of ON/OFF, volume, balance and tone facilities (supplied as standard)
- Clear LED level indicator / setting status display
- Screw terminations on the rear of the unit for loudspeakers, power and wired line input
- Separate loudspeaker balance adjustment to allow system set up (control located on rear of unit)
- Includes Plugtop Power Supply
- Also includes Wallmounted Bracket for remote control



Systems also feature:  
**IR Remote Control**



Systems also feature:  
**Remote Wall Bracket**



Available Accessories:  
**AVID S BOX Surface-mount BackBox**



Available Accessories:  
**AVID IL 2xRCA~3.5mm Stereo Lead (1.5m)**



Also available as complete systems:



- **AVID SYSTEM W:** Featuring 2 x 15W, 8Ω wallmount loudspeakers.



- **AVID SYSTEM C:** Featuring 2 x 6W, 8Ω ceiling loudspeakers.

**Specifications:**

Model:	AVID
Output Power	2 x 12W RMS @ 8Ω
Line Inputs	Stereo Phonos (L & R) Stereo 3.5mm Jack (priority) Screw Terminal (Rear PCB in parallel with 3.5mm Jack Input)
Frequency Response	40Hz ~ 20KHz
Input Sensitivity	200mV/1V
Power Requirements	24V DC, 1.25A
Dimensions	165(W) x 100(H) x 35(D) mm
Weight	0.26kg

[www.cie-group.com](http://www.cie-group.com)

CIE-Group Widdowson Close Blenheim Ind Est Bulwell Nottingham NG6 8WB England  
T: +44(0)115 9770075 F: +44(0)115 9770081 E: info@cie-group.com W: www.cie-group.com

**cie-group**  
A better way to buy AV