



Clever Little Box



AVID SYSTEM-C: In-wall Stereo Amplifier System with 2 x Ceiling Speakers

The AVID System-C includes AVID Compact In-Wall Stereo Amplifier and accessories, together with 2 x 6W Ceiling Loudspeakers.

The AVID In-wall Amplifier from Clever Little Box is a stylish, but discreet 2 x 12W stereo amplifier for in-wall or dado conduit mounting.

An ideal solution for AV and single-room voice or sound reinforcement applications, the AVID Stereo Amplifier is fitted into a 2-gang wallplate and features 3 x audio source inputs (3.5mm jack, 2 x RCA and screw terminals), line level sensitivity switch and bright LED display.

Supplied as standard, the AVID remote control unit provides ON/OFF, volume, tone and balance control.

The AVID compact amplifier is ideal for applications such as classrooms, boardrooms, meeting or demo rooms and even in domestic home installations.

Features:

- Stereo amplifier fitted to UK 2-gang Wallplate
 - New higher power 2 x 12W output (RMS)
 - 3 x Input Sources: Stereo Phono, 3.5mm Stereo Jack (Jack has priority and Wired Input Terminal (on rear PCB)
 - Line Level Sensitivity Switch
 - Control of ON/OFF and volume via illuminated push button located on the front panel
 - Infrared remote control of ON/OFF, volume, balance and tone facilities (supplied as standard).
 - Clear LED level indicator/setting status display
 - Screw terminations on the rear of the unit for Loudspeakers, power and wired line input
 - Separate Loudspeaker balance adjustment to allow system set up (control located on rear of unit)
 - Includes Plugtop Power Supply
 - Also includes Wallmounted Bracket for remote control
- Supplied with 2 x 6W 8" ceiling Loudspeakers



Systems also feature:
IR Remote Control



Systems also feature:
Remote Wall Bracket



Available Accessories:
AVID S BOX Surface-mount BackBox



Available Accessories:
AVID IL 2xRCA~3.5mm Stereo Lead (1.5m)



Specifications:

Model:	AVID SYSTEM-C
Output Power	2 x 12W RMS @ 8Ω
Line Inputs	Stereo Phonos (L&R); Stereo 3.5mm Jack (priority); Screw Terminal (rear PCB in parallel with 3.5mm Jack Input)
Frequency Response	40Hz ~ 20kHz
Input Sensitivity	100mv/1v
Power Requirements	24v DC, 1.25A
Dimensions	165(W) x 100(H) x 35(D) mm
Weight (Net)	1.26kg
Weight (Gross)	2.08kg

www.cie-group.com

CIE-Group Widdowson Close Blenheim Ind Est Bulwell Nottingham NG6 8WB England
T: +44(0)115 9770075 F: +44(0)115 9770081 E: info@cie-group.com W: www.cie-group.com

cie-group
A better way to buy AV