

# CLOCKAUDIO

## C850E SHOTGUN SUPERCARDIOID MICROPHONE

Designed for use in Broadcast,  
Film/Video Recording and Theatre  
Sound Reinforcement.



- Smooth Response for consistent sound quality
- Superior Grade Components
- Balanced output
- Selectable Bass Roll Off and 10dB pad
- XLR Termination
- Finished in Satin Black

PROFESSIONAL  
MICROPHONE  
SYSTEMS





## C850E SHOTGUN SUPERCARDIOID MICROPHONE

## SPECIFICATIONS

### C850E

TYPE	Condenser (Back electret)	
POLAR PATTERN	Supercardioid	
FREQUENCY RESPONSE	50Hz - 20KHz	
SENSITIVITY	-48dB +/-3dB @ 1KHz (0db = 1V/Pa)	
IMPEDANCE	200 Ohms	
S/N RATIO	68dB (A)	
MAXIMUM SPL	126dB THD 1%	
POWER REQUIREMENTS	9 - 48 Volts Phantom Power	
SWITCHABLE BASS FILTER	-4dB Per Octave at 400Hz to -6dB Per Octave at 100Hz	
TERMINATION	Male 3 Pin XLR	
FINISH	Satin Black	
ACCESSORIES	Windshield and Stand Adaptor fitted with Camera Shoe 5/8" Stand Thread	
DIMENSIONS	21mm (0.83 ins.)	238mm (9.3 ins.)
NETT/SHIPPING WEIGHT	216 gms (7.6 ozs.)	525 gms (18.5 ozs.)
PACKING	350mm x 130mm x 50mm (13.7 ins. x 5.1 ins. x 2.0 ins.)	



## CLOCKAUDIO

9 Stratfield Park, Elettra Avenue, Waterlooville, Hampshire PO7 7XN  
Tel +44 (0)23 9225 1193 Fax +44 (0)23 9225 1201  
E-mail [sales@clockaudio.demon.co.uk](mailto:sales@clockaudio.demon.co.uk) [www.clockaudio.demon.co.uk](http://www.clockaudio.demon.co.uk)

