

- **DM105/CT:** Five-zone Paging Microphone
- **DM110/CT:** Ten-zone Paging Microphone

Incorporating 'soft-touch' zone selection, 'Press-to-Talk' and 'All-Call' switches to ensure no pops or clicks are heard when activated. LED indicators are provided to show the user which zone has been selected.

The elegant, yet robust gooseneck allows the user to position the microphone in the optimum position for high quality speech reproduction.

Soft plastic feet stop the units from slipping around the reception desk/counter surface when being used and 'key hole' slots are provided on the base to allow wall mounting.

Designed to operate with conventional relay switch systems, both versions are supplied with 1.5m 15-way 'D' type-to-open end leads, making installation quick and simple.

**Features:**

- 5/10 zone paging
- All Call
- Flexible Robust Gooseneck
- Wall mounting feature



**Specifications:**

Model:	DM105/CT	DM110/CT
Output Sensitivity	Mic Level: 1mv Line Level: 500mv	Mic Level: 1mv Line Level: 500mv
Output Impedance	Mic Level: 60Ω Line Level: 600Ω	Mic Level: 60Ω Line Level: 600Ω
Characteristics	Polar diagram approx to cardioid, presence lift @ 3kHz	Polar diagram approx to cardioid, presence lift @ 3kHz
Frequency Response	±6dB, 100Hz ~ 8kHz	±6dB, 100Hz ~ 8kHz
'Press-to-Talk'/'All Call'	'Soft touch' momentary action push button	'Soft touch' momentary action push button
Zone Selection	'Soft touch' latching action	'Soft touch' latching action
Terminations	15 Way 'D' male to unterminated open end (1.5m)	15 Way 'D' male to unterminated open end (1.5m)
Finish	Desk top: grey Desk base: satin black powder coat Gooseneck & mic: matt black	Desk top: grey Desk base: satin black powder coat Gooseneck & mic: matt black
Dimensions	Base: 130(W) x 50(H) x 170(D) mm Gooseneck length to capsule: 260mm	