

- **GDS-RFID READER: USB RFID Card Reader**

The USB RFID Card Reader is available for use with the GDS3710 and GDS3705 IP Video Door Intercom Stations.

The GDS-RFID Card Reader can be installed anywhere and connects via USB to any computer running Grandstream's free GDS Manager software to allow all RFID Card Reader activity to be tracked, monitored and managed centrally by GDS Manager.

The device is fully powered through USB and offers a built-in antenna with card-seeking mode.

**Features:**

- Registration/Management of RFID cards per user, for use with GDS3710 & GDS3705 IP Intercoms
- Connects to PC via USB (supplied)
- For use with Grandstream 'GDS Manager' free software
- USB Powered
- Compatible with Grandstream GDS-RFID CARDS and GDS-RFID FOBS



**Specifications:**

<b>Model:</b>	<b>GDS-RFID CARD</b>
Card Supported	Generic RFID card
Working Frequency	125KHz
Power Supply	5v DC (±4%)
Electric Current	Stand-by Current 20mA; Operation Current <35mA
Working Temperature	-10°C ~ 70°C
Storage Temperature	-20°C ~ 80°C
USB Cable Length	1.5 metres
Dimensions	108.5(H) x 108.5(W) x 24(D) mm, ±3mm
Net. Weight	0.12kg