



## Multi-Frequency Receiver

IL-AC-WM-2C-00

Multi-frequency receivers with 1,000 selectable UHF frequencies (672.000-696.975MHz) for each channel (10 groups with 100 channels each).

This receiver has 2 channels. A 4 channel receiver is also available (IL-AC-WM-4C-00).

### Physical Data

Dimensions (boxed)	Height - 45mm (1.77") Width - 482mm (18.98") Depth - 195mm (7.68")
Weight	1.8kg (3.97lbs)
Finish	Black

### Technical Data

Carrier frequency	672.000-696.975 MHz
RF S/N ratio	105 dB
Audio frequency range	30-18,000 Hz
THD	< 0.5 %
Dynamic range	120 dB
Audio output	350 mV/600 $\Omega$ (jack)
	25 mV/600 $\Omega$ (XLR, bal.)
Admiss. ambient temp.	0-40 °C
Power supply	Plug-in PSU

### Features

- Automatic scan
- True diversity system with removable antennas (BNC connection)
- Volume and squelch can be adjusted for each channel
- LCD for group/channel, antenna A/B, RF transmitting level, AF audio level and additional LED level display for audio level of each channel
- XLR output for each channel, bal.
- 6.3mm output for mixed signal
- Supplied with power supply unit
- 482mm (19") rack installation

Talk to us now:

T: +44 (0)115 977 0075

E: [info@cie-group.com](mailto:info@cie-group.com)

[www.cie-group.com](http://www.cie-group.com)

