



Paragon 264x4-16 – 16-channel D1 real time H.264 digital video recorder



Delivery includes IR remote control!

Features

- D1 real time recording and playback for all cameras
- HDMI video output with full HD resolution (1080p)
- Latest H.264 compression technology
- User-friendly GUI (GUI) with easy mouse or front panel operation
- Multi-language menu operation
- Express setup for quick installation in standard applications
- Audio recording for all 16 channels
- Separately configured HDMI 1080p and VGA/BNC main monitor outputs and additional call monitor output
- Individual recording and schedule settings for each channel incl. holiday calendar, express schedule and pre-alarm
- Pentaplex operation for simultaneous recording, playback, archiving, live view and network access
- Snapshot search function
- Data archiving via USB 2.0 port, network or built-in DVD-RW drive*
- Programmable motion detection area (22x16) for each channel
- Local (through USB mouse) and network PTZ control
- Fast network video transmission with dual stream for mobile phone streaming
- Network operation independent from local operation
- Event notification incl. e-mail alarm and network alarm with optional PowerCon 4.x software (from version 4.3)
- Watchdog function with notification options
- Optional RS-485 remote control (EKB 500)
- Free EverFocus DDNS service: DDNS account registration directly from DVR setup

* feature / function depending on DVR model

Technical data	
Video format	PAL / CCIR
Display format main monitor	VGA / BNC: 1, 4, 9, 10, 13, 16x multiscreen, PiP // HDMI: 1, 4, 6, 8, 9, 12, 16x multiscreen
Display format call monitor	Full screen, 4x multiscreen, sequence (live)
Display format HD monitor	1920 x 1080 (full HD 1080p)
Display format VGA monitor	1024 x 768
Main/call monitor assignment	Option 1: main monitor VGA and BNC (simultaneous view) and call monitor HDMI Option 2: main monitor HDMI and call monitor VGA and BNC (simultaneous view)
Video input	16 inputs 1 Vp-p composite PAL, BNC, automatic 75 Ohm termination
Video output	16 loop-through outputs, 1 Vp-p at 75 Ohm, BNC / 1 main monitor output, 1 Vp-p at 75 Ohm, BNC / 1 main monitor output VGA 800x600, 15-pin Sub-D / 1 call monitor output, 1 Vp-p at 75 Ohm, BNC / 1 HDMI output 1920 x 1080 (1080p)
Video compression	H.264
Harddisk storage	Up to 4x internal 8,9 cm (3,5") SATA harddisks OR up to 2x removable 8,9 cm (3,5") SATA harddisks*
Recording resolution	704 x 576, 704 x 288, 352 x 288
Recording rate	1 ~ 400 IPS for all resolutions Individual setup per channel for normal and event recording (remaining rate to be distributed among remaining channels)
Recording modes	Continuous, schedule (with holiday calendar) or event recording
Playback search	Via date/time or event / smart search incl. snapshot search function
Video pause	Yes
Video loss detection	Yes
Motion detection	Yes, with configurable detection area (22x16) and sensitivity
Event log	Yes
Pre-alarm	Yes
Alarm	16 alarm inputs / 4 relay outputs
Audio	16 line inputs / 1 line output
Setup	On-screen display
Control	USB mouse control, front panel control with jog/shuttle, IR remote control, network; optional: RS-485 keyboard EKB 500
Timer	Built-in real time clock with automatic time synchronisation via global NTP server through Internet
Title	12-characters title generator for each camera
Archive	USB 2.0 interface, internal DVD-RW drive*
Ethernet	RJ45 network connector
Interfaces	1 x RS-232 (9-pin Sub-D) // 1 x RS-485 screw terminal connector
Password protection	3 levels
Watchdog function	For cooler fan, HDD status, HDD temperature, recording and HDD fault
Power source	100 ~ 240 V AC
Power consumption	60 W max.
Ambient temperature	0°C ~ +40°C
Dimensions (WxHxD)	430 x 95 x 410 mm
Weight	6,8 kg (w/o HDD)

Paragon_264x4-16_db_en_rev02

Remote control devices

EKB 500 – multi-function keyboard



Technical data

Keys	48
Joystick	3D PTZ function control
Jog/shuttle	DVR control
Display	LCD 2 lines with 20 characters each
Baud rate	1.200 ~38.400
Serial interfaces	RS-232 (service) / 2 x RS-485
Protocols	Pelco-P / Pelco-D / EverFocus / ED 2200 / ED 2250
Devices	Control of speed dome, DVR and EQ 2700 motorzoom camera
Cascading	Up to 8 keyboards addressable
Wiring box	Yes
Power source	12 V DC, via included power supply 230 V AC
Power consumption	10 W max.
Ambient temperature	0°C ~ +40°C
Dimensions (WxHxD)	360 x 110 x 200 mm
Weight	1,5 kg

Ordering information

EPARA 264x4-16-FIA / NH	16-channel D1 real time H.264 DVR Paragon, w/o harddisk, with audio function, w/o DVD-RW drive , 100 ~ 240 V AC Harddisk storage: optional up to 4x built-in 8,9 cm (3,5") SATA HDD
EPARA 264x4-16-DIA / NH	16-channel D1 real time H.264 DVR Paragon, w/o harddisk, with audio function, with DVD-RW drive , 100 ~ 240 V AC Harddisk storage: optional up to 4x built-in 8,9 cm (3,5") SATA HDD
EPARA 264x4-16-FRA / NH	16-channel D1 real time H.264 DVR Paragon, w/o harddisk, with audio function, w/o DVD-RW drive , 100 ~ 240 V AC Harddisk storage: optional up to 2x removable 8,9 cm (3,5") SATA HDD
EPARA 264x4-16-DRA / NH	16-channel D1 real time H.264 DVR Paragon, w/o harddisk, with audio function, with DVD-RW drive , 100 ~ 240 V AC Harddisk storage: optional up to 2x removable 8,9 cm (3,5") SATA HDD
EKB 500	Multi-function keyboard for speed dome and DVRs, with 3-axis joystick and jog/shuttle, 12 V DC (230 VAC power supply incl.)

Please order your Paragon DVR as follows:

DVR Series / Model / No. of harddisks / Size of harddisks / Example:

Ordering code:

→ You'll receive:

EPARA 264x4 16-DIA / 3 / 500 → 16-channel Paragon DVR with built-in DVD-RW drive, audio function and 3 built-in 500 GB HDD
 EPARA 264x4 16FRA / 2 / 1000 → 16-channel Paragon DVR w/o DVD-RW drive, with audio function and 2 built-in 1000 GB HDD (removable)

If you prefer to receive the DVR and HDDs separately, please order the respective "NH" DVR model and separate harddisks in the requested size. If you prefer to receive the DVR without any harddisks, we'll provide you with a list of suitable harddisks which have been tested and approved for your Paragon 264x4 DVR.