

○ R150+ / R300+ / R500+ : Reference Series Low Impedance Amplifiers

A series of 2 channel, convection-cooled (no fans) low impedance amplifiers. The units are ideal for 'silent' systems in church, audio visual and recording studios, etc. Simple controls and visual clip/signal/protection LEDs complete a versatile, cost effective package.

Features:

- Convection cooled
- Stereo operation (4/8Ω)
- Bridged mono operation (8Ω)
- Inputs (XLR~1/4" jack)
- Outputs (speakon~binding posts)
- Mains powered
- 2U high, 19" rack mounting

Specifications:

Model:	R150+:	R300+:	R500+:
Output Power/Per Channel	50W @8Ω, 75W @4Ω	100W @8Ω, 150W @4Ω	160W @8Ω, 250W @4Ω
Output Power/Bridged Mono	150W @8Ω	300W @8Ω	500W @8Ω
Input/Sensitivity	0dB/0.775mV	0dB/0.775mV	0dB/0.775mV
Frequency Response	20Hz ~ 20KHz	20Hz ~ 20KHz	20Hz ~ 20KHz
Power Requirement	230V AC 50Hz	230V AC 50Hz	230V AC 50Hz
Dimensions	482(W) x 88(H) x 317(D)mm	482(W) x 88(H) x 317(D)mm	482(W) x 88(H) x 317(D)mm
Weight	7.2kg	8.4kg	10.4kg

